totflex

PRODUCT DATASHEET

Sprinkler Hose & Connection Set

Braided stainless sprinkler connection - hose, bracket and fittings as one kit

TECHNICAL DATA

NOMINAL SIZE	DN20 / DN25 (3/4"·1") hose; other sizes to order
WORKING PRESSURE	Up to approx. 16 bar system pressure (rated per the applicable listing; test p
HOSE	AISI 304 / 316L corrugated stainless core with stainless braid
HOSE LENGTH	Approx. 700·1800 mm; longer lengths made to order
INLET	1" or 3/4" threaded / nipple (BSP, NPT or customer standard)
OUTLET	1/2" or 3/4" reducer to suit the sprinkler head
BENDS	Multiple bends within the assembly's rated minimum bend radius
SERVICE	Ambient wet-system duty in the building's protected spaces

TYPES & CONFIGURATIONS

REDUCED BORE	Standard set for typical head flows
FULL BORE	Full-flow hydraulic designs
LENGTHS	700 - 1800 mm, longer to order
APPROVALS	FM / UL / VdS / LPCB versions

STANDARDS

FM / UL / VdS / LPCB listings - installed to NFPA 13 / 13R / 13D and local codes

sales@totflex.net - +90 216 306 40 44 - totflex.net

TOTFLEX - a brand of TOTALIEN Endustriyel Urunler San. Tic. Ltd. Sti. - Manufactured in Turkiye, exported worldwide