

The logo for Totflex features the brand name in a bold, red, sans-serif font. The text is centered within a white, diamond-shaped area that is superimposed on a background of diagonal grey lines. The overall design is framed by a red border, with a central vertical strip containing a black and white wavy pattern.

Totflex

Totflex

DIRECT OUTPUT LEVEL INDICATORS_TLG DO



TLG 30



TLG Direct Output



TLG Boiler Type



TLG Elec. Resistance

Advantage of our products:

- Stainless steel structure help us to use in corrosive conditions and variety application areas.
- Possible to acquiring either analog or digital output according to application.
- Flanged, threaded, standard or special connection options
- High temperature resistance flaps
- Real-time liquid level control
- Like Magnetic Level Indicators, with output can be integrated into the automation and Start-Stop, Alarm can be received with 4-20mA or 0-10V output.
- If requested, it is possible to manufacture models with valves and display scale.

Are of use

All steam and hot water boilers
Waste water systems
Filling and unloading containers
All chemical and petrochemical tanks
Tanks for petroleum and petroleum products
Oil boilers
Diesel fuel tanks and generator sets
Submarine, helicopter and ship fuel tanks

Totflex

TLG Standart LEVEL INDICATORS



TLG Standart



TLG Scale



TLG Valve



TLG Top Mounted

Advantage of our products:

- Stainless steel structure help us to use in corrosive conditions and variety application areas.
- Possible to acquiring either analog or digital output according to application.
- Flanged, threaded, standard or special connection options
- High temperature resistance flaps
- Real-time liquid level control
- Like Magnetic Level Indicators, with output can be integrated into the automation and Start-Stop, Alarm can be received with 4-20mA or 0-10V output.
- If requested, it is possible to manufacture models with valves and display scale.

Are of use

All steam and hot water boilers
Waste water systems
Filling and unloading containers
All chemical and petrochemical tanks
Tanks for petroleum and petroleum products
Oil boilers
Diesel fuel tanks and generator sets
Submarine, helicopter and ship fuel tanks

Totflex

Technical Specifications:

Technical Properties	Models			
	TLG Standart	TLG Scale	TLG Valve	TLG Top Mounted
Pressure	PN10			
Temperature	Max 200 °C		Max 150 °C	Max 200 °C
Connection Material	Carbon Steel , Stainless Steel			
Connection Type	G 1/2", 3/4", 1" Flange DN15, DN20, DN25			FLANGE DN150
Pipe & Float	Stainless Steel			
Indicator	Aluminum			
Magnetic Rollers	Nylon 6 rollers			
Scale	PP Opac Printing onto Aluminum Section			

Totflex

Soganlik Yeni Mah. Ataturk Cad.
No: 6/1 Else Apt. Kat: 8 Daire: 9
Istanbul-Turkey
Tel: 0216 306 40 44

sales@totflex.net
www.totflex.net